

EVERBUILD 565 CLEAN ROOM SILICONE

DECLARATION OF PERFORMANCE

No. 565WE/2-CPR/2018

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	565WE
2	INTENDED USE/S	Sealants for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for façade; Sealants for exterior and interior applications Part 3: Sealants for sanitary joints; Sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water
3	MANUFACTURER:	EVERBUILD BUILDING PRODUCTS LTD Site 41, Knowsthorpe Ways, Cross Green Industrial Estate, Leeds, LS9 0SW, UK
4	AUTHORISED REPRESENTATIVE:	Not applicable
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15651-1 and 3
	Notified body/ies:	1213

Declaration of Performance

565WE

565WE/2-CPR/2018

2018.07 , ver. 01

1213

7a DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Release of dangerous chemicals	See SDS		
Reaction to fire	Class E		
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10%		
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 100%		
Tensile properties (ISO8339) for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	≤ 0.9 MPa		EN 15651-1
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 100%		
Durability	Pass		

Declaration of Performance

565WE
 565WE/2-CPR/2018
 2018.07 , ver. 01
 1213



7b DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Release of dangerous chemicals	See SDS		
Reaction to fire	Class E		
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10%		
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 100%		EN 15651-3
Microbiological Growth	0		
Durability	Pass		


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
 Function: Technical Product Co-ordinator
 At Leeds on 16 July 2018

Name : Andrew Stockill
 Function: QA / QC Supervisor
 At Leeds on 16 July 2018




End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

565WE
 565WE/2-CPR/2018
 2018.07 , ver. 01
 1213





Everbuild Building Products LTD, Leeds, UK

DoP No. 565WE/2-CPR/2018

EN 15651-1

Notified Body 1213

Sealants for non-structural use in the joints in buildings and pedestrian walkways for Sealants for exterior and interior applications

Release of dangerous chemicals	See SDS
Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 100%
Tensile properties (ISO8339) for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	≤ 0.9 MPa
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 100%
Durability	Pass

[for DoP see www.everbuild.co.uk](http://www.everbuild.co.uk)

Declaration of Performance

565WE
565WE/2-CPR/2018
2018.07 , ver. 01
1213





Everbuild Building Products LTD, Leeds, UK

DoP No. 565WE/2-CPR/2018

EN 15651-3

Notified Body 1213

Sealants for non-structural use in the joints in buildings and pedestrian walkways for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurized water

Release of dangerous chemicals	See SDS
Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 100%
Microbiological Growth	0
Durability	Pass

for [DoP see www.everbuild.co.uk](http://www.everbuild.co.uk)

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

565WE
565WE/2-CPR/2018
2018.07 , ver. 01
1213

Declaration of Performance

565WE

565WE/2-CPR/2018

2018.07, ver. 01

1213

