

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Everbuild Technic Sealent Primer P1

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company
Site 41
Knowsthorpe Way
Cross Green Industrial Estate
Leeds
West Yorkshire LS9 0SW
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|--|
| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapour. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Reproductive toxicity, Category 2 | H361d: Suspected of damaging the unborn child. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Specific target organ toxicity - repeated exposure, Category 2 | H373: May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters air- |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

ways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

| | |
|-------|--|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters air-ways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Precautionary statements :

Prevention:

| | |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face protection. |

Response:

| | |
|---------------------------|---|
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P305 + P351 + P338 + P310 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. |
| P331 | Do NOT induce vomiting. |
| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

Hazardous components which must be listed on the label:

- 203-625-9 toluene
- 200-751-6 butan-1-ol
- 202-615-1 n-butyl methacrylate
- 201-297-1 methyl methacrylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name CAS-No. EC-No. Registration number | Classification (REGULATION (EC) No 1272/2008) | Concentration [%] |
|--|--|----------------------|
| toluene 108-88-3 203-625-9 01-2119471310-51-XXXX | Flam. Liq.2; H225 Skin Irrit.2; H315 Repr.2; H361d STOT SE3; H336 STOT RE2; H373 Asp. Tox.1; H304 | >= 50 - <= 100 |
| butan-1-ol 71-36-3 200-751-6 01-2119484630-38-XXXX | Flam. Liq.3; H226 Acute Tox.4; H302 Skin Irrit.2; H315 Eye Dam.1; H318 STOT SE3; H335, H336 | >= 3 - < 5 |
| n-butyl methacrylate 97-88-1 202-615-1 | Flam. Liq.3; H226 Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Skin Sens.1; H317 | >= 1 - < 2,5 |
| methyl methacrylate 80-62-6 201-297-1 01-2119452498-28-XXXX | Flam. Liq.2; H225 STOT SE3; H335 Skin Irrit.2; H315 Skin Sens.1; H317 | >= 1 - < 2,5 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

sue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

Risks : Risk of serious damage to the lungs (by aspiration).
irritant effects
sensitising effects

May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

| Components | CAS-No. | Value | Control parameters * | Basis * |
|---------------------|----------|-------|----------------------------------|---------|
| toluene | 108-88-3 | TWA | 50 ppm 191 mg/m ³ | GB EH40 |
| | | STEL | 100 ppm 384 mg/m ³ | GB EH40 |
| butan-1-ol | 71-36-3 | STEL | 50 ppm 154 mg/m ³ | GB EH40 |
| methyl methacrylate | 80-62-6 | STEL | 100 ppm 416 mg/m ³ | GB EH40 |
| | | TWA | 50 ppm 208 mg/m ³ | GB EH40 |

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm),

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),

breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : colourless
Odour : aromatic
Odour Threshold : No data available
Flash point : ca. 8 °C
Autoignition temperature : 355 °C
Decomposition temperature : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

| | |
|--|---------------------------------------|
| Lower explosion limit (Vol-%) : | 1 %(V) |
| Upper explosion limit (Vol-%) : | 7 %(V) |
| Flammability : | No data available |
| Explosive properties : | No data available |
| Oxidizing properties : | No data available |
| pH : | No data available |
| Melting point/range / Freezing point : | No data available |
| Boiling point/boiling range : | No data available |
| Vapour pressure : | 28,9975 hPa |
| Density : | ca.0,95 g/cm ³ at 20 °C |
| Water solubility : | slightly soluble |
| Partition coefficient: n-octanol/water : | No data available |
| Viscosity, dynamic : | No data available |
| Viscosity, kinematic : | > 7 mm ² /s at 40 °C |
| Relative vapour density : | No data available |
| Evaporation rate : | No data available |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Country GB 100000011374

8 / 13

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017

Version 0.0



BUILDING TRUST



Print Date 27.07.2017

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

butan-1-ol:

Acute oral toxicity : LD50 Oral (Rat): ca. 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.430 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

SECTION 14: Transport information

ADR

- 14.1 UN number** : 1993
14.2 UN proper shipping name : FLAMMABLE LIQUID, N.O.S.
(toluene, butan-1-ol)
14.3 Transport hazard class(es) : 3
14.4 Packing group : II
Classification Code : F1
Labels : 3
Tunnel restriction code : (D/E)
14.5 Environmental hazards : no

IATA

- 14.1 UN number** : 1993
14.2 UN proper shipping name : Flammable liquid, n.o.s.
(toluene, butan-1-ol)
14.3 Transport hazard class(es) : 3
14.4 Packing group : II
Labels : 3
14.5 Environmental hazards : no

IMDG

- 14.1 UN number** : 1993
14.2 UN proper shipping name : FLAMMABLE LIQUID, N.O.S.
(toluene, butan-1-ol)
14.3 Class : 3
14.4 Packing group : II
Labels : 3
EmS Number 1 : F-E
EmS Number 2 : S-E
14.5 Marine pollutant : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted (toluene)

REACH - Candidate List of Substances of Very High : None of the components are listed

Country GB 100000011374

11 / 13

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017

Version 0.0



Print Date 27.07.2017

Concern for Authorisation (Article 59). (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

| | | Quantity 1 | Quantity 2 |
|------------------|-------------------|------------|------------|
| P5c | FLAMMABLE LIQUIDS | 5.000 t | 50.000 t |
| VOC-CH (VOCV) | : 53 % | | |
| VOC-EU (solvent) | : 53 % | | |

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

| | |
|-------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Everbuild Technic Sealent Primer P1

Revision Date 27.07.2017



BUILDING TRUST



Version 0.0

Print Date 27.07.2017

Full text of other abbreviations

| | |
|-------------|--|
| Acute Tox. | Acute toxicity |
| Asp. Tox. | Aspiration hazard |
| Eye Dam. | Serious eye damage |
| Eye Irrit. | Eye irritation |
| Flam. Liq. | Flammable liquids |
| Repr. | Reproductive toxicity |
| Skin Irrit. | Skin irritation |
| Skin Sens. | Skin sensitisation |
| STOT RE | Specific target organ toxicity - repeated exposure |
| STOT SE | Specific target organ toxicity - single exposure |
| ADR | Accord européen relatif au transport international des marchandises Dangereuses par Route |
| CAS | Chemical Abstracts Service |
| DNEL | Derived no-effect level |
| EC50 | Half maximal effective concentration |
| GHS | Globally Harmonized System |
| IATA | International Air Transport Association |
| IMDG | International Maritime Code for Dangerous Goods |
| LD50 | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | Occupational Exposure Limit |
| PBT | Persistent, bioaccumulative and toxic |
| PNEC | Predicted no effect concentration |
| REACH | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | Substances of Very High Concern |
| vPvB | Very persistent and very bioaccumulative |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !