



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

**No: HYBSMP/1-CPR/ 2014**

Substrate: Anodised aluminium and Mortar M1

Primer: No primer on Aluminium, Sikaflex Primer 3-N for Mortar

1. Identification Code	<b>Everbuild TECNIC HYRIFLEX SMP</b>  <b>Codes: FPHYBSMP</b>
2. Type, Batch and/or Serial Number	<b>- For batch number - see packaging</b>
3. Intended use	<b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 3</b>
7. Notified Body and Tasks	<b>SKZ Notified Body No. 1213</b>
8. European Technical Assessment	<b>Not Applicable</b>
9. Declared Performance	<b>TO EN15651-1 (2012)</b>
Type	<b>F EXT-INT-CC</b>
Classification	<b>F25HM</b>



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

Reaction to Fire	<b>Class E</b>
Loss of Volume ISO10563	<b>≤10%</b>
Resistance to flow ISO7390	<b>≤3 mm</b>
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	<b>NF</b>
Adhesion/cohesion properties ISO 8340 modified (-30°C)	<b>NF</b>
Durability ISO 8340, ISO 9047 and ISO 10590	<b>Pass</b>

Substrate: Anodised aluminium and Mortar M1

Primer: No primer on Aluminium, Sikaflex Primer 3-N for Mortar

1. Identification Code	<b>Everbuild TECNIC HYRIFLEX SMP</b>  <b>Codes: FPHYBSMP</b>
2. Type, Batch and/or Serial Number	<b>- For batch number - see packaging</b>
3. Intended use	<b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 3: Sealants for Sanitary elements</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 3</b>



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

7. Notified Body and Tasks	<b>SKZ Notified Body No. 1213</b>
8. European Technical Assessment	<b>Not Applicable</b>
9. Declared Performance	<b>TO EN15651-4 (2012)</b>
Type	<b>PW EXT-INT-CC</b>
Classification	<b>PW25HM</b>
Reaction to Fire	<b>Class E</b>
Loss of Volume ISO10563	<b>≤10%</b>
Resistance to flow ISO7390	<b>≤3 mm</b>
Adhesion/cohesion properties at maintained extension (23°C) ISO 8340	<b>NF</b>
Tear Resistance ISO 8340 modified	<b>NF</b>
Adhesion / Cohesion properties at maintained extension 28 days water immersion (23°C) ISO 10590 modified	<b>NF change of secant modulus: ≤50%</b>
Adhesion / Cohesion properties at maintained extension 28 days salt water immersion (23°C) ) ISO 10590 modified	<b>NF</b>
Adhesion/cohesion properties at maintained extension (-30°C) ISO 8340 modified	<b>NF</b>
Durability ISO 8340, ISO 9047 and ISO 10590	<b>Pass</b>

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Site 41, Knowsthorpe Way,  
Cross Green Industrial Estate, Leeds, LS9 0SW  
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424  
Fax: +44 (0) 113 240 0024  
e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)  
website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Two handwritten signatures in blue ink. The first signature is 'I.G. Southerington' and the second is 'P.R. Thomas'.

Dated: Leeds, 12/6/14